



MAIN FEATURES

- Highest efficiency
- Nominal RF power 50W, 100W, 300W, 500W, 1000W
- Very low signal noise typ. -80 dB
- High stereo performance typ. 60 dB
- Extremely low distortion 0,01%
- Completely broadband
- 6th LD-MOS generation VSWR 65:1
- Large LCD color display with touch panel
- AC mains 90-260 VAC extend range with PFC
- CCIR & FCC compliant
- Remote Control through mobile APP
- Web server

OPTIONS

- AES/EBU
- RDS/RBDS coder
- SNMP remote control
- OIRT and JPN version
- Audio IP
- Digital device



EVOLUTION
TOUCH



SOFTWARE
ENERGY SAVING



FULL AUDIO
INTERFACE



MOBILE REMOTE
CONTROL

TECHNICAL SPECIFICATIONS



GENERAL	Power Output	50W (typ. 60W), 100W (typ. 110W), 500W (typ. 550W), 1000W (typ. 1100W) adjustable from front panel
	RF Output Impedance	50 ohm
	RF Output Connector	"N"(50-100-300W), "7/16"(500-1000W) type
	Monitor RF	BNC connector
	VSWR	1,5:1 WITH AUTOMATIC FOLDBACK
	Frequency Range	87.5 ÷ 108.00 MHz, on request 66 ÷ 74 MHz (OIRT) 76 ÷ 90 MHz (JPN) Programmable in 1 Hz steps
	Frequency Stability	±1 ppm from -5 to 45°C
	External Reference	10 MHz BNC connector back panel
	Type of Modulation	Analog
	Off Lock Attenuation	≥ -80 dBc
	Modulation Capability	±150 KHz
	Limiter built in	
	Power Good Detector	adjustable from 20÷90% of the power
	Audio Presence Detector	adjustable time from front panel
	External AGC	Automatic, with fine ADJ back panel
	Modulation Mode	Mono, Stereo, Multiplex, SCA, RDS, Aux
	Preemphasis	Flat/50/75µs selectable from front panel
	Asynchronous AM S/N Ratio	-60 dB
	Synchronous AM S/N Ratio	-60 dB
	RF Harmonics	Exceeds EBU/CCIR/FCC requirements
	RF Spurious	Exceeds EBU/CCIR/FCC requirements
MONO OPERATION	Audio Input Impedance	600 ohm - 10 Kohm balanced
	Audio Input Level	-6 to +12 dBm
	Input Connector	XLR female
	Audio Frequency Response	±0.1 dB, 20 Hz to 15 KHz
	Total Harmonic Distortion + Noise	0.01% @ 400 Hz
	Intermodulation Distortion	0.01%, 1 KHz/1.3 KHz, 1:1 ratio
	Transient Intermodulation Distortion	0.01% 2.96KHz square wave and 14 KHz sine wave
	Distortion	0.01% 2.96KHz square wave and 14 KHz sine wave
	FM S/N Ratio	-80 dB below ±75 KHz dev.
STEREO OPERATION	Audio Input Impedance	600 ohm - 10 Kohm balanced
	Audio Input Level	-6 to +12 dBm
	Input Connector	XLR female
	Audio Frequency Response	±0.1 dB, 20 Hz to 15 KHz
	Total Harmonic Distortion + Noise	0.01% @ 400 Hz
	Intermodulation Distortion	0.01%, 1 KHz/1.3 KHz, 1:1 ratio
	Transient Intermodulation Distortion	0.01% 2.96KHz square wave and 14 KHz sine wave
	FM S/N Ratio	-80 dB below ±75 KHz dev.
	Stereo Separation	20 Hz ÷ 15 KHz ≥ -60dB
	Crosstalk attenuation	Main to Sub -70 dB 30 Hz to 15 KHz
	38 KHz Suppression	≥ -85 dB
	Pilot Frequency	19 KHz ± 1 Hz
	Output Pilot	1 Vpp., BNC female

TECHNICAL SPECIFICATIONS

MULTIPLEX OPERATION	Composite Input Impedance		2 Kohm unbalanced
	Composite Input Level		-6 to +12 dBm
	Input Connector		BNC female
	Composite Amplitude Response		±0.1 dB, 30 Hz to 100 KHz
	Total Harmonic Distortion + Noise		0.01% @ 400 Hz
	Intermodulation Distortion		0.01%, 1 KHz/1.3 KHz, 1:1 ratio
	Transient Intermodulation Distortion		0.01% 2.96KHz square wave and 14 KHz sine wave
	FM S/N Ratio		-80 dB below ±75 KHz deviation
AES/EBU OPERATION	Input Connector		XLR female, optical TOS-LINK
	Input Impedance		110 ohm
	Input Level		-20 to +0 dBfs
	Data Format		S/PDF, AES/EBU, IEC958, EIAJCP340/1201
	Sampling Frequency		from 32 to 96 KHz
SCA, RDS, AUX OPERATION	Input Impedance		≥ 2 Kohm
	Input Level		-6 to +12 dBm
	Frequency Response		±0.1 dB, 50 KHz to 100 KHz
	Input Connector		BNC female
AUXILIARY CONNECTIONS	RS485		DB9 connector back panel
	Telemetry Interface		connector DB25 back panel
	LAN		RJ45 connector back panel
	MPX OUT		connector BNC back panel
OPTIONS			AES/EBU -SPDIF
			RDS/RBDS Programmable Coder via PC
			OIRT or JPN version
			SNMP
			Audio IP
ELECTRICAL	AC Input Power		90+260 VAC 50/60 HZ single phase
	AC Apparent Power Consumption		100VA @ 50W, 200VA @ 100W, 450VA @ 300W, 750VA @ 500W, 1400VA @ 1000W
	Cos Ø		> 0.98
	Cooling		Forced air
	Acoustic noise		< -56 dBa @ 1 meter
ENVIRONMENTAL	Operating temperature		-5°C to +50°C
	Max Operating Altitude		2000 mt
	Relative Humidity Range		0 to 90%
PHYSICAL DIMENSION	Mounting		Standard 19" chassis 2 U rack
	Size		W x 483 mm. D x 470 mm. H x 88 mm
	Weight		~ 6,0 Kg. (50-100w), 8Kg. (300-500-1000W)